

[Open in app](#)[Get started](#)

Ginny Fahs

[Follow](#)Apr 15, 2018 · 2 min read · [Listen](#)[Save](#)

GitHub Error: Authentication Failed from the Command Line

After setting up 2 Factor Authentication on GitHub, I couldn't push my remote repositories from the command line anymore.

When I tried to push a remote repo, the command line threw this error:

```
~ :> git push origin my-branch  
  
Username for 'https://github.com': myusername  
  
Password for 'https://myusername@github.com': mypassword  
  
remote: Invalid username or password.  
  
fatal: Authentication failed for 'https://github.com/my-repository'
```

The error stumped me — and made me vow that, when I did ultimately get to the bottom of it, I'd do my best to pay the knowledge forward.

How to Authenticate on GitHub with 2FA

Command line authentication requires a personal access token.


Go to Settings:






Open in app

Get started



Then Developer Settings:



Then Personal access tokens:





Open in app

Get started

Settings / Developer settings

- OAuth Apps
- GitHub Apps
- Personal access tokens

No OAuth applications

OAuth applications are used to access the GitHub API. [Read the docs](#) to find out more.

[Register a new application](#)

© 2018 GitHub, Inc. [Terms](#) [Privacy](#) [Security](#) [Status](#) [Help](#)



[Contact GitHub](#) [API](#) [Training](#) [Shop](#) [Blog](#) [About](#)

Generate a new Personal Access Token. Make sure you copy the Personal Access Token as soon as it gets generated — you won't be able to see it again!

Search GitHub Pull requests Issues Marketplace Explore

Settings / Developer settings

- OAuth Apps
- GitHub Apps
- Personal access tokens

Personal access tokens

[Generate new token](#) [Revoke all](#)

Tokens you have generated that can be used to access the [GitHub API](#).

username admin:org, admin:org_hook, admin:public_key, admin:repo_hook, repo, user	Last used within the last 2 weeks	Edit	Delete
username admin:gpg_key, admin:org, admin:org_hook, admin:public_key, admin:repo_hook, gist, notifications, repo, user	Last used within the last week	Edit	Delete
username gist, public_repo	Never used	Edit	Delete
username admin:public_key	Last used within the last 2 months	Edit	Delete

Personal access tokens function like ordinary OAuth access tokens. They can be used instead of a password for Git over HTTPS, or can be used to [authenticate to the API over Basic Authentication](#).

Paste the Personal Access Token into the “Password” field when you authenticate via the command line.



[Open in app](#)[Get started](#)

```
Username for 'https://github.com': myusername
Password for 'https://myusername@github.com': ← Here :)
remote: Invalid username or password.
fatal: Authentication failed for 'https://github.com/my-repository'
```

GitHub has published official instructions for this flow [here](#) (though without glam screenshots...)

Hope this helps — happy coding!

[About](#) [Help](#) [Terms](#) [Privacy](#)

Get the Medium app

